

Motorové kondenzátory, SR Passives

SRPASSIVES



Typ kondenzátora	polypropylénový
Prac. napätie	450 V
Tolerancia	±5%
Klimatická kategória	25/70/21
Životnosť	3000 h
Pracovná teplota	-25...70°C

Symbol	Kap. [μF]	Rozm. tel. [mm]	Symbol	Kap. [μF]	Rozm. tel. [mm]
CBB60E-1/450	1	Ø30x57	CBB60A-12/450	12	Ø40x70
CBB60A-1.5/450	1,5	Ø30x60	CBB60E-12/450	12	Ø40x70
CBB60E-1.5/450	1,5	Ø30x57	CBB60A-14/450	14	Ø40x70
CBB60A-2/450	2	Ø30x60	CBB60E-14/450	14	Ø40x70
CBB60E-2/450	2	Ø30x57	CBB60H-14/450	14	Ø42x70
CBB60A-2.5/450	2,5	Ø30x60	CBB60A-16/450	16	Ø40x70
CBB60E-2.5/450	2,5	Ø30x57	CBB60E-16/450	16	Ø40x70
CBB60G-2.5/450	2,5	Ø35x65	CBB60G-16/450	16	Ø40x70
CBB60H-2.5/450	2,5	Ø35x60	CBB60H-16/450	16	Ø42x70
CBB60G-3/450	3	Ø35x65	CBB60A-20/450	20	Ø40x70
CBB60H-3/450	3	Ø35x60	CBB60E-20/450	20	Ø40x70
CBB60E-4/450	4	Ø35x65	CBB60G-20/450	20	Ø40x70
CBB60H-4/450	4	Ø35x60	CBB60H-20/450	20	Ø40x70
CBB60A-4.5/450	4,5	Ø35x60	CBB60E-25/450	25	Ø42x95
CBB60E-4.5/450	4,5	Ø35x60	CBB60G-25/450	25	Ø45x95
CBB60A-6/450	6	Ø35x60	CBB60H-25/450	25	Ø42x82
CBB60E-6/450	6	Ø35x65	CBB60A-30/450	30	Ø45x90
CBB60G-6/450	6	Ø35x65	CBB60E-30/450	30	Ø45x90
CBB60H-6/450	6	Ø35x60	CBB60G-30/450	30	Ø45x95
CBB60A-8/450	8	Ø35x60	CBB60H-30/450	30	Ø50x90
CBB60E-8/450	8	Ø35x65	CBB60A-40/450	40	Ø48x93
CBB60F-8/450	8	Ø35x60	CBB60E-40/450	40	Ø50x106
CBB60G-8/450	8	Ø35x65	CBB60A-50/450	50	Ø50x106
CBB60H-8/450	8	Ø35x60	CBB60E-50/450	50	Ø50x106
CBB60A-10/450	10	Ø35x60	CBB60A-60/450	60	Ø50x106

CBB60E-10/450	10	Ø35x65	CBB60E-60/450	60	Ø50x106
CBB60G-10/450	10	Ø35x65	CBB60A-80/450	80	Ø58x120
CBB60H-10/450	10	Ø35x60	CBB60E-80/450	80	Ø60x120
			CBB60E-100/450	100	Ø60x120

Vývody:

- konektory 6,3mm ([CBB60E-xxx/450](#), [CBB60A-xxx/450](#))
- očkové M4 ([CBB60G-xxx/450](#), [CBB60F-8/450](#))
- vodiče ([CBB60G-xxx/450](#), [CBB60H-xxx/450](#), [CBB60F-8/450](#))

Upevnenie ([CBB60E-xxx/450](#), [CBB60G-xxx/450](#)):

- skrutka M8

Dĺžka kábla ([CBB60G-2.5/450](#), [CBB60G-20/450](#), [CBB60G-3/450](#), [CBB60G-30/450](#), [CBB60G-6/450](#), [CBB60G-8/450](#), [CBB60G-10/450](#), [CBB60G-16/450](#), [CBB60H-25/450](#)):

- 190 mm